

SAFETY LABEL

Manufacturer: NORSK KLEBER
 Skansen 29, Otta, Norway
Model: Merethe⁺
Variant:
Serial:

Date of Manufacture:
 Tested to UL 1482-2011

NOT APPROVED FOR USE IN MOBILE HOMES
Install and Use in Accordance with Norsk Kleber Installation and Assembly Instructions only
FOR USE WITH SOLID WOOD FUEL ONLY.
Do Not Connect This Unit to a Chimney Flue Serving Another Appliance
Inspect and Clean Chimney Frequently-Under Certain Conditions of Use, Creosote Buildup



CAUTION

HOT WHILE IN OPERATION DO NOT TOUCH, KEEP CHILDREN, CLOTHING AND FURNITURE AWAY MAY CAUSE SKIN BURNS SEE NAME PLATE AND INSTRUCTIONS

PREVENT HOME FIRES: Contact Local Building and Fire Officials About restrictions in your Area.
NORSK KLEBER requires installation and assembly by trained professionals only.



C US File No. 19-478


Minimum Clearances to Combustible Materials

Models with Windows

SW	Sidewall to Side	19"	(48 cm)
SFC	Sidewall to Flue Collar	25.5"	(65 cm)
BW	Backwall to Side	17"	(43 cm)
BFC	Backwall to Flue Collar	19"	(48 cm)

No Windows

SW	Sidewall to Side	17"	(43 cm)
SFC	Sidewall to Flue Collar	23.5"	(60 cm)
BW	Backwall to Side	17"	(43 cm)
BFC	Backwall to Flue Collar	19"	(48 cm)



Chimney Connection


Use 6" flue connector
 Made from 24 gage or heavier steel

Chimney Connector Clearances

The stove position will be determined by the greater of either the stove clearance or the chimney connector clearance above (X) and to the side (Y).

X Connector to Ceiling 19" Y Connector to Parallel Wall 19"

Rear Exit Chimney
 Connector Clearance



Protection

* measured from the door opening

A	B	C	D	E
29 1/2" 750mm	8" * 203 mm	33 3/4" 857 mm	16" 406 mm	2" 51mm

Floor Protection Extension From Corner

	C / I	F	L
Stove Clearance to Wall:	16"	8 1/2"	6"
Stove Depth from Corner:	58 1/2"	47 3/4"	44 1/4"

